



Prime-Tek 11 A-Side

White

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 07/03/2014

Revision date: 04/08/2015

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Prime-Tek 11 A-Side Epoxy Primer White
 Product code : 11A-X5, 11A-GL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Epoxy Primer (Mixture when A & B sides are combined)

1.3. Details of the supplier of the safety data sheet

Coating & Foam Solutions, LLC
 1100 Cottonwood Ave. Suite 300
 Hartland, WI 53029
 (888) 284-7488

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irritation 2
 Eye Irritation 2A
 Skin Sensitisation 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
 Contains materials suspected of causing cancer (bound in liquid/paint, not airborne dust).

Precautionary statements (GHS-US) :

Wash hands thoroughly after handling. Wear protective gloves/ eye protection/face protection.
 Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	30 - 60	Not classified
Bisphenol A-epichlorohydrin polymer	(CAS No) 25068-38-6	10 - 45	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Titanium dioxide**	(CAS No) 13463-67-7	0.5 - 1.5	Carc. 2**

Safety Data Sheet

Name	Product identifier	%	GHS-US classification
Ethylene oxide	(CAS No) 75-21-8	< 0.1	Flam. Gas 1, H220 Press. Gas, H280 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H335
1,4-Dioxane	(CAS No) 123-91-1	< 0.1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
Acetaldehyde	(CAS No) 75-07-0	< 0.1	Flam. Liq. 1, H224 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

** These materials are bound in liquid/paint and are not airborne or in dust form.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitisation by skin contact.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

Safety Data Sheet

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Precautions for safe handling : Avoid contact with skin and eyes. Do not swallow. Avoid breathing vapour or mist. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Wash hands before eating, drinking, or smoking. Launder contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Limestone (1317-65-3)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total); 5 mg/m ³ (resp)

Bisphenol A-epichlorohydrin polymer (25068-38-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m ³)	Not applicable.

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

Ethylene oxide (75-21-8)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1047)

1,4-Dioxane (123-91-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Acetaldehyde (75-07-0)		
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Safety glasses or goggles are recommended when handling product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid.
Appearance	: Viscous.
Colour	: White.
Odour	: Faint aromatic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: > 100 °C (> 212 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 1.405
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: 6500 - 12000 cPs
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity : Not classified

Prime-Tek 11 A-Side	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available.

Safety Data Sheet

Limestone (1317-65-3)	
LD50 oral rat	6450 mg/kg
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 oral rat	13600 mg/kg
LD50 dermal rabbit	>20mL/kg
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg
Ethylene oxide (75-21-8)	
LD50 oral rat	72 mg/kg
LC50 inhalation rat	800 ppm/4h
1,4-Dioxane (123-91-1)	
LD50 oral rat	4200 mg/kg
LD50 dermal rabbit	7600 mg/kg
LC50 inhalation rat	48.5 mg/L/4
Acetaldehyde (75-07-0)	
LD50 oral rat	1930 mg/kg
LC50 inhalation rat	13300 ppm/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans (airborne, unbound particles of respirable size)
Ethylene oxide (75-21-8)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
	In OSHA Specifically Regulated Carcinogen list
1,4-Dioxane (123-91-1)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Acetaldehyde (75-07-0)	
IARC group	1 - Carcinogenic to humans, 2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Safety Data Sheet

SECTION 12: Ecological information**12.1. Toxicity**

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability**Prime-Tek 11 A-Side**

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

12.3. Bioaccumulative potential**Prime-Tek 11 A-Side**

Bioaccumulative potential	No additional information available.
---------------------------	--------------------------------------

12.4. Mobility in soil**Prime-Tek 11 A-Side**

Ecology - soil	No additional information available.
----------------	--------------------------------------

12.5. Other adverse effects

Other adverse effects : No additional information available.

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information**15.1. US Federal regulations**

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Ethylene oxide (75-21-8)

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
--	------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

1,4-Dioxane (123-91-1)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

Acetaldehyde (75-07-0)

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
--------------------------	--

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

15.2. US State regulations**Prime-Tek 11 A-Side**

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	---

SECTION 16: Other information

Date of issue	: 07/03/2014
Revision date	04/08/2015
Version	1.0
Data sources	: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Other information	: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

COATING & FOAM SOLUTIONS, LLC (CFS)

THIS INFORMATION AND TECHNICAL ADVICE PROVIDED HEREIN ARE BELIEVED TO BE RELIABLE AND ACCURATE TO THE BEST KNOWLEDGE OF CFS, AS BASED ON TESTS AND SHOULD SERVE ONLY AS A RECOMMENDATION. AS THE MANUFACTURER, CFS MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESSED, IMPLIED OR STATUTORY, INCLUDING BUT NOT LIMITED TO ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR USE OR A PARTICULAR PURPOSE FOR THE PRODUCT. CFS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE RESULTS OF THE USE OF THE PRODUCT AND ASSUMES NO OBLIGATION OR LIABILITY IN CONNECTION THEREWITH. CFS IS NOT LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY SORT FROM USE OF THIS PRODUCT. THE INFORMATION PROVIDED HEREIN IS SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE. INFORMATION CHANGES MAY INCLUDE, BUT ARE NOT LIMITED TO, COMMERCIAL AND TECHNICAL CHANGES, CHANGES IN PRICING, PHYSICAL CHARACTERISTICS AND PACKAGING.