

Prime-Tek 11 B-Side

Dark Gray

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom (HCS) 2012, GHS 2013

Date of issue: 07/03/2014 Revision date: 07/02/2015 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form Mixture

Product name : Prime-Tek 11 B Side Epoxy Primer Dark Gray

Product code : 11B-X5, 11B-GL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Epoxy Primer (Mixture when A & B sides are combined)

1.3. Details of the supplier of the safety data sheet

Coating & Foam Solutions, LLC 1100 Cottonwood Ave., Suite 300 Hartland, WI 53029 (888) 284-7488

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquids 4 Skin Irritation 2 Serious Eye Damage 2A Skin Sensitisation 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS07

GHS

Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: Combustible liquid. Causes skin irritation. Causes serious eye damage/irritation. May cause an allergic skin reaction. Contains materials suspected of causing cancer (bound in liquid/paint, not

airborne dust).

Precautionary statements (GHS-US)

: Keep away from flames and hot surfaces. - No smoking. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Dispose of contents and container in accordance with all local, regional, national and

international regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	30 - 60	Not classified
Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines	(CAS No) 68410-23-1	5 - 20	Skin Irrit. 2, H315 Eye Dam. 2A, H319/H370 Skin Sens. 1, H317

Prime-Tek 11 B-Side

Dark Gray

Safety Data Sheet

Name	Product identifier	%	GHS-US classification
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	5 - 20	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox 1 H304
Carbon black**	(CAS No) 1333-86-4	0.1 - 1	Carc. 2**

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing

and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

If a configuration of the NOT is the account of the state of the state

First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of

the skin. May cause sensitisation by skin contact.

Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva. May cause burns.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal

Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid

breathing vapour or mist. Do not swallow. Handle and open container with care. When using do

not eat, drink or smoke.

Hygiene measures : Wash hands before eating, drinking, or smoking. Launder contaminated clothing before reuse.

Orig.: 08/15/2014 Rev.: 7/2/2015 EN (English) SDS Prime-Tek 11 B-Side 2/6

^{**} These materials are bound in liquid/paint and are not airborne or in dust form.

Safety Data Sheet

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place.

Keep cool.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Limestone (1317-65-3)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total);
		5 mg/m³ (resp)

Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines (68410-23-1)		
USA ACGIH	ACGIH TWA (mg/m³)	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m³)	Not applicable.

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA (mg/m³)	Not applicable.
USA OSHA	OSHA PEL (TWA) (mg/m³)	Not applicable.

Carbon black (1333-86-4)		
USA ACGIH	ACGIH TWA (mg/m³)	3 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m³

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face

shield) protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must

be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety

practices

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid. Appearance Viscous. Colour : Dark gray. Odour : Aromatic, strong. Odour threshold No data available. рН No data available. Relative evaporation rate (butylacetate=1) No data available. Melting point : No data available. Freezing point : No data available. Boiling point No data available. Flash point : > 60 °C (> 140 °F) Self ignition temperature : No data available. Decomposition temperature : No data available. Flammability (solid, gas) : Flammable.

Safety Data Sheet

Vapour pressure : No data available. Relative vapour density at 20 °C : No data available.

Relative density : 1.394

Solubility : No data available. Log Pow : No data available. No data available. Log Kow Viscosity, kinematic : No data available. 70000 - 150000 cPs Viscosity, dynamic Explosive properties : No data available. Oxidising properties : No data available. **Explosive limits** No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Prime-Tek 11 B-Side	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available.

Limestone (1317-65-3)

LD50 oral rat 6450 mg/kg

Fatty acids, C18-unsaturated, dimers, reaction products with Polyethylenepolyamines (68410-23-1)		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rat	> 2000 mg/kg	

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	>5.2 mg/L/4h

Carbon black (1333-86-4)		
	LD50 oral rat	>15400 mg/kg
	LD50 dermal rat	>3000 mg/kg

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage/eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Dark Gray

Safety Data Sheet

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans (airborne, unbound particles of respirable size)
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met
Symptoms/injuries after inhalation	May cause respiratory tract irritation.
Symptoms/injuries after skin contact	Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking the skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking an tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/injuries after ingestion	May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Prime-Tek 11 B-Side		
	Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

Prime-Tek 11 B-Side	
Bioaccumulative potential	No additional information available.

12.4. Mobility in soil

Prime-Tek 11 B-Side	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Other adverse effects : No additional information available. Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

In accordance with DOT: Roof Coating, Not Regulated.

(49CFR: Applicable for domestic transportation by highway and rail, **but not air or vesse**l) (See 49CFR 173.150(F)(1).

Non bulk packaging (less than 119 gallons), material ships as non-regulated. (See 49CFR 173.150(F)(2).

14.1. UN number for AIR, VESSEL or INTERNATIONAL

UN1993

14.2. UN proper shipping name

Proper Shipping Name : Flammable Liquid, n.o.s.

Hazard Classes : 3
Packing group : III

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

Prime-Tek 11 B-Side

Dark Gray

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. US State regulations

Prime-Tek 11 B-Side		
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.	

SECTION 16: Other information

 Date of issue
 : 07/03/2014

 Revision date
 : 07/02/2015

Version : 2.0

Data sources : SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom

2012.

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

COATING & FOAM SOLUTIONS, LLC. (CFS)

THIS INFORMATION AND TECHNICAL ADVICE PROVIDED HEREIN ARE BELIEVED TO BE RELIABLE AND ACCURATE TO THE BEST KNOWLEDGE OF CFS AS BASED ON TESTS AND SHOULD SERVE ONLY AS A RECOMMENDATION. AS THE MANUFACTURER, CFS MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESSED, IMPLIED OR STATUTORY, INCLUDING BUT NOT LIMITED TO ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR USE OR A PARTICULAR PURPOSE FOR THE PRODUCT. CFS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE RESULTS OF THE USE OF THE PRODUCT AND ASSUMES NO OBLIGATION OR LIABILITY IN CONNECTION THEREWITH. CFS IS NOT LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY SORT FROM USE OF THIS PRODUCT. THE INFORMATION PROVIDED HEREIN IS SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE. INFORMATION CHANGES MAY INCLUDE, BUT ARE NOT LIMITED TO, COMMERCIAL AND TECHNICAL CHANGES, CHANGES IN PRICING, PHYSICAL CHARACTERISTICS AND PACKAGING.

Orig.: 08/15/2014 Rev.: 7/2/2015 EN (English) SDS Prime-Tek 11 B-Side 6/6